

# Quantum Computing with Very Noisy Gates

Produced with pdflatex and xfig

- The  $C_4/C_6$  architecture.
- Performance data from simulation.
- Resource requirements.

E. “Manny” Knill: [knill@boulder.nist.gov](mailto:knill@boulder.nist.gov)

# Fault-Tolerant Quantum Computing

- **Requirement 3 for scalable QC<sup>a</sup> implementation:**  
Sufficiently low noise affecting physical gates and memory.  
DiVincenzo (2000) [4]
- *Error model*: The type of noise affecting a QC implementation.
- *Fault-tolerant architecture*: A scheme for scalable QC in the presence of noise.
- Fundamental problems of FTQC<sup>b</sup>:
  1. Scalable QC with error model  $\mathcal{E}$ ?
  2. Scalable QC with fault-tolerant architecture  $\mathcal{A}$  and with  $\mathcal{E}$ ?
- Practical problems of FTQC<sup>b</sup>:
  1. Can computation  $\mathcal{C}$  be implemented with a given error and device budget?

<sup>a</sup> Quantum Computing.

<sup>b</sup> Fault-Tolerant Quantum Computing

# On Noise Thresholds

## Fault-Tolerance Threshold Theorem.

- Thresholds depend on:
  - Error model
  - Available devices.
  - Geometrical constraints.
  - ...

$$\vec{0} \leq \text{threshold} < \vec{1}$$

- Threshold studies yield:
  - Fault-tolerant engineering strategies.
  - Guidelines for gate-error/geometry/resource trade-offs.
- Thresholds are asymptotic.
  - Thresholds are not “observable”.
- Thresholds hide resource tradeoffs.




# In Other Words...

---

- Thresholds are too optimistic.
  - Error budget near threshold → impractical resources.
  - ... try to do better by one to two orders of magnitude.
- Thresholds are too pessimistic.
  - Most bounds/estimates are based on specific, concatenated architectures.
  - Large computations/simulations/fundamental tests may be implementable anyway.  
E.g. rare-error kickback may be deferred.
  - ... there is no non-idealized threshold.




# Constructing Quantum Computers



- Fault-tolerant architectures:  
physical qubits,gates  $\Rightarrow$  near-perfect logical qubits, gates.
- Common structural assumptions:
  - Remaining errors are not removable by physical engineering.
  - Physical qubits and gates are nearly independent.
  - Physical gates can be applied in parallel.
  - Any number of physical qubits can be used, subject to geometrical constraints.



# Error Models I



- General error expansion:

$$\begin{aligned}
 & \sum \dots + \text{[Circuit Diagram]} \otimes |e_a\rangle \\
 & \dots + \dots + \text{[Circuit Diagram]} \otimes |e_c\rangle + \dots \\
 & = \sum_e \sum_{\mathbf{p}=(p_i)_i} |e_{\mathbf{p}}\rangle_{\text{Env}} \prod_i \overbrace{G_i}^{\text{Gate } i} \underbrace{E_i(p_i)}_{\text{Pauli product at location } i}
 \end{aligned}$$

Unnormalized “environment” state



# Error Models II

$$= \sum_e \sum_{\mathbf{p}=(p_i)_i} \underbrace{|e_{\mathbf{p}}\rangle_{\text{Env}}}_{\text{Unnormalized "environment" state}} \prod_i \overbrace{G_i}^{\text{Gate } i} \underbrace{E_i(p_i)}_{\text{Pauli product at location } i}$$

- Assume temporal and spatial independence:  
Total amplitude of errors simultaneously affecting  $k$  given locations decays exponentially with  $k$ .
- Further idealizing assumptions:
  - Errors are probabilistic Pauli ( $|e_p\rangle$  are orthogonal).  
Justification: The randomization conjecture.
  - Errors at different locations are statistically independent.  
Justification: Increase physical separations or delocalize logical qubit encodings.



# Two Error Trade-offs

---

- Preparation and measurement error requirements are benign.  
Justification: Given good CNOTs, use classical error-correction and detection methods to reduce preparation and measurement errors.

- Long “measurement” times and feed-forward delays require very good quantum memories.

Explanation: Feedforward circuits require delaying for measurement outcomes.

Note: Feedforward loop does not require amplifying the measurement outcome for human consumption.

$$(\text{memory error rate}) * (\text{feed-forward delay}) \ll 1.$$





# The $C_4/C_6$ Architecture: Features


---

- Use the simplest error-detecting codes and concatenation.
- Exploit error-correcting teleportation.
- Postselected quantum computing for state preparation.
- Partial decoding for state preparation.
- Fault-tolerant implementation of Clifford gates +  $\delta$  suffices.
- Evidence that depolarizing errors  $> 3\%$  per CNOT\* are ok.

\* error  $\epsilon/\text{CNOT} \equiv \frac{4\epsilon}{5}/\text{one-qubit gate}, \frac{4\epsilon}{15}/\text{preparation or measurement},$   
no geometrical constraints.



# Typical Resource Requirements




- Resource overheads\* for the  $C_4/C_6$ -architecture and different computation sizes (by simulation and modelling).

\* Order-of-magnitude, extrapolated.




# $C_4/C_6$ concatenation hierarchy.



# Error-correcting Teleportation


- Syndrome measurement from qubit-wise teleportation.



- Syndrome  $\rightarrow$  error detection, correction, tracking.
- Use *Pauli frame* to avoid explicit correction gates.




# Post-selected State Preparation




- Error in the prepared state  $\equiv$  error in the input state.
- States only need to be “good” conditional on error checks.
  - Residual errors + input + Bell measurement errors must be correctable.
- Can use parallel state preparation factories.




# $C_4$ Bell-State Preparation




Logical qubits teleportation:




Implementations:




# $C_4$ Bell-State Preparation




Logical qubits teleportation:




Implementations:




# $C_4$ Bell-State Preparation



Logical qubits teleportation:



Implementations:





# Postselected Quantum Computing

---

- Postselected quantum computers.
  - Can execute any of the basic operations, but
  - an operation may fail, possibly destructively.
  - If an operation fails, this is announced.... exponentially small success probability (not 0) is possible.
- A postselected QC is fault-tolerant if  
success  $\rightarrow$  negligible probability of error.
- A postselected FTQC only needs to detect errors.
- Does postselected FTQC imply FTQC?  
... Nearly: Use postselected FTQC to prepare key states.



# Power of Clifford-Pauli Operations


- The CSS operations,  $\mathcal{CSS}$ :  
Preparation of  $|0\rangle$  and  $|+\rangle$ , CNOT, measurement of  $X$  and  $Z$ .  
– CSS operations suffice for encoding/decoding CSS codes.
- Universal quantum computation is possible with  $\mathcal{CSS}$ ,  $H$  and  $|\pi/8\rangle$ -preparation.

$$\text{QC} = \overbrace{\mathcal{CSS}}^{\subseteq \mathcal{N}} + \underbrace{\text{"}\epsilon\text{"}}_H + \underbrace{\text{"}\delta\text{"}}_{|\pi/8\rangle}.$$

- A fault-tolerant computation strategy:
  1. Implement a fault tolerant CSS computer, i.e. arbitrarily accurate logical  $\mathcal{CSS}$  with feedforward.
  2. + "  $\epsilon$  " + "  $\delta$  " ...  
 + "  $\delta$  ":  $|\pi/8\rangle$  purification using good  $\mathcal{CSS}$  + "  $\epsilon$  "  
 Bravyi&Kitaev (2004) [1], Knill (2004) [2]
- $\text{FT}\mathcal{CSS}$  and  $(|\pi/8\rangle \text{ error}) \leq (|0\rangle, |+\rangle \text{ error}) \Rightarrow \text{FTQC?}$



## In Other Words...



1. Build a device that supports a very good CSS-based (or similar) quantum memory for (say) three logical qubits.
2. Ensure that neighboring devices can exchange logical qubits.
3. Implement quantum gates internally to a device at leisure.  
⇒ the devices can form a quantum computer.



# Simulation of the $C_4/C_6$ Architecture



1. Computer-assisted heuristics to arbitrarily high levels.
  - Error-model propagation to detect rare-error kickbacks.
2. Monte-Carlo simulation to determine  $C_4/C_6$  error behavior up to level 4.

Implementation issues:


- Avoid transients:  
Verify error behavior of the second operation.
- Verify full error behavior:  
Operate on one-half of an entangled pair.
- Verify that errors do not compound:  
Check on a long sequence of operations.
- Architecture is not strictly concatenated:  
Full simulations at high levels.
- Keep track of resources used.



# Error Probabilities for Scalable QC



# Conclusion



- Can my computation (or simulation or fundamental test) be implemented with a given error and device budget?

# Contents

Title: Quantum Computing.....	0	Post-selected State Preparation.....	12
Fault-Tolerant Quantum Computing.....	1	$C_4$ Bell-State Preparation I.....	13
On Noise Thresholds.....	2	$C_4$ Bell-State Preparation II.....	14
In Other Words.....	3	$C_4$ Bell-State Preparation III.....	15
Constructing Quantum Computers.....	4	Postselected Quantum Computing.....	16
Error Models I.....	5	Power of Clifford-Pauli Operations.....	17
Error Models II.....	6	In Other Words.....	18
Two Error Trade-offs.....	7	Simulation of the $C_4/C_6$ Architecture.....	19
The $C_4/C_6$ Architecture: Features.....	8	Error Probabilities for Scalable QC.....	20
Typical Resource Requirements.....	9	Conclusion.....	21
$C_4/C_6$ concatenation hierarchy.....	10	References.....	23
Error-correcting Teleportation.....	11		



# References

- [1] S. Bravyi and A. Kitaev. Universal quantum computation based on a magic states distillation. quant-ph/0403025, 2004.
- [2] E. Knill. Fault-tolerant postselected quantum computation: Schemes. quant-ph/0402171, 2004.
- [3] D. Gottesman. *Stabilizer Codes and Quantum Error Correction*. PhD thesis, Calif. Inst. Tech, Pasadena, California, 1997.
- [4] D.P. DiVincenzo. The physical implementation of quantum computation. *Fort. Phys.*, 48:771–783, 2000.
- [5] P. W. Shor. Scheme for reducing decoherence in quantum computer memory. *Phys. Rev. A*, 52:2493–2496, 1995.
- [6] P. W. Shor. Fault-tolerant quantum computation. In *Proceedings of the 37th Symposium on the Foundations of Computer Science (FOCS)*, pages 56–65, Los Alamitos, California, 1996. IEEE press.
- [7] A. Yu. Kitaev. Quantum computations: Algorithms and error correction. *Russian Math. Surveys*, 52:1191–1249, 1997.
- [8] D. Aharonov and M. Ben-Or. Fault-tolerant quantum computation with constant error. In *Proceedings of the 29th Annual ACM Symposium on the Theory of Computation (STOC)*, pages 176–188, New York, New York, 1996. ACM Press.
- [9] E. Knill, R. Laflamme, and W. H. Zurek. Resilient quantum computation. *Science*, 279:342–345, 1998.
- [10] A. M. Steane. Overhead and noise threshold of fault-tolerant quantum error correction. *Phys. Rev. A*, 68:042322/1–19, 2003.
- [11] E. Knill. Fault-tolerant postselected quantum computation: Threshold analysis. quant-ph/0404104, 2004.
- [12] E. Knill. Quantum computing with realistically noisy devices. *Nature*, 434:39–44, 2005.
- [13] B. W. Reichardt. Improved ancilla preparation scheme increases fault tolerant threshold. quant-ph/0406025, 2004.
- [14] J. P. Clemens, S. Siddiqui, and J. Gea-Banacloche. Quantum error-correction against correlated noise. preprint, 2004.
- [15] B. M. Terhal and G. Burkard. Fault-tolerant quantum computation for local non-markovian noise. quant-ph/04020104, 2004.
- [16] R. Alicki. Comments on "fault-tolerant computation for local non-markovian noise. quant-ph/0402139, 2004.
- [17] E. Knill. Scalable quantum computation in the presence of large detected-error rates. *Phys. Rev. A*, 71:042322/1–7, 2005.

